




## A 19 Spezial

100 % PTFE Fiber with Unique Blocking Agent

### Characteristics

- In applications with high pressure or vacuum, die formed bullrings of S4 (no food approval) are recommended
- Very low coefficient of friction and displays low stem/spindle frictions
- Long lifetime
- No ageing
- Minimized maintenance and readjustment

### Operating range

			
p [psi]	360	3630	7250
v [fpm]	390	300	
t °F	-330 ... +540		
pH	0 - 14		
lb/in <sup>3</sup>	0.0578		

### Main application

- Valves
- Fittings
- Gate valves
- Flaps
- Plunger
- Door and lid seals

### Suitable for

- Pulp and paper industry
- Chemical industry
- General Industry



### Form of delivery

This packing can be manufactured from 3 to 40 mm / 1/8" to 1.5" square as well as in intermediate, inch sizes and special measurements.

03-09 mm/1/8"-5/16" on 2 lbs spool  
10-15 mm/3/8"-9/16" on 5 lbs spool  
16-25 mm/5/8"-1" on 10 lbs spool

Special length, pre-cut or die formed rings on request.

1 lbs of packing of the following cross-sections is equivalent to displayed lengths in feet:

Size	Feet	Size	Feet
3 [1/8"]	85.4	13 [1/2"]	5.8
4	58.1	14 [9/16"]	4.7
5 [3/16"]	37.2	15	4.1
6	25.8	16 [5/8"]	3.6
6.4 [1/4"]	23.1	18	2.9
8 [5/16"]	14.5	19 [3/4"]	2.6
9.5 [3/8"]	10.3	20	2.3
10	9.3	22 [7/8"]	1.9
11 [7/16"]	7.5	25 [1"]	1.5
12	6.5		

All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.

Please note that the technical values cannot be used all at the same time in their maximum values.

### ProPack AG

Rudolf-Diesel-Ring 28 . 82054 Sauerlach . Germany

Phone ++49 (0) 8104 6640 0 . Fax ++49 (0) 8104 6640 44

propack@propack.ag

[www.propack.ag](http://www.propack.ag)

TECHNOLOGY MADE IN GERMANY