






A 44 I Grapho Extra

Braid of Flexible Expanded Graphite Tape Reinforced with Inconel Wire

Characteristics

- Universal use valve packing
- Expanded graphite of higher quality
- Coefficient of expansion similar to steel
- For valve applications rings should be approx. 20 - 25 % compressed at installation
- Precompressed rings are recommended

Operating range

			
p [psi]	0	0	4350
v [fpm]	0	0	
t °F	-330 ... +1020		
pH	0 - 14		
lb/in ³	0.0434		

Practical useful application data:
max. temperature in oxidizing
atmosphere: +750 °F

Main application

- Valves
- Fittings
- Gate valves
- Flaps
- Door and lid seals

Suitable for

- Power plant technology
- Petrochemical plants
- Boiler houses
- High pressure- and high temperature applications
- For higher pressure and temperature applications use suitable bullrings.



Form of delivery

This packing can be manufactured from 3 to 40 mm / 1/8" to 1.5" square as well as in intermediate, inch sizes and special measurements.

03-09 mm/1/8"-5/16" on 2 lbs spool
10-15 mm/3/8"-9/16" on 5 lbs spool
16-25 mm/5/8"-1" on 10 lbs spool

Special length, pre-cut or die formed rings on request.

1 lbs of packing of the following cross-sections is equivalent to displayed lengths in feet:

Size	Feet	Size	Feet
3 [1/8"]	120.9	13 [1/2"]	8.2
4	82.3	14 [9/16"]	6.7
5 [3/16"]	52.7	15	5.9
6	36.6	16 [5/8"]	5.1
6.4 [1/4"]	32.7	18	4.1
8 [5/16"]	20.6	19 [3/4"]	3.6
9.5 [3/8"]	14.6	20	3.3
10	13.2	22 [7/8"]	2.7
11 [7/16"]	10.7	25 [1"]	2.1
12	9.1		

All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time. Please note that the technical values cannot be used all at the same time in their maximum values.

ProPack AG

Rudolf-Diesel-Ring 28 · 82054 Sauerlach · Germany

Phone ++49 (0) 8104 6640 0 · Fax ++49 (0) 8104 6640 44
propack@propack.ag

www.propack.ag
TECHNOLOGY MADE IN GERMANY