



S 73 - HT 1050

Silicafiber Packing

Characteristics

- Non flammable
- High electric- and thermal isolation capability
- Dimensionally stabil
- Good mechanical structural strength
- Low shrinkage
- Low Volumeloss

Operating range

t °C	-100 ... +1,050
pH	3 - 9

Temperature: short term up to +1,100 °C

Main application

- Furnace, boiler and chimney doors
- Expansion joints
- Exhaust pipes

Suitable for

- Power plant
- Furnace construction

Form of delivery

- Braided in square X-Section
- On request some X-Sections with 0.12 mm V4A wire reinforcement.

Square X Section

Standard dimensions / Sales unit

Size	Weight [g/m]	Sales unit [m]
08 x 08	58	100
10 x 10	95	100
12 x 12	140	50
15 x 15	180	50
16 x 16	200	50
20 x 20	353	50
25 x 25	540	25
30 x 30	780	25



All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.

Please note that the technical values cannot be used all at the same time in their maximum values.

ProPack AG

Rudolf-Diesel-Ring 28 . 82054 Sauerlach

Fon ++49 (0) 8104 6640 0 . Fax ++49 (0) 8104 6640 44

propack@propack.ag

www.propack.ag

TECHNOLOGY MADE IN GERMANY

