





P 83

Cotton with tallow/grease and Run In Lubricant

Characteristics

- Universal packing for the lower temperature range
- Excellent value for money
- Recommended shaft surface hardness: HRC 45
- Excellent in products containing solids

Operating range

			
p [bar]	20	50	50
v [m/s]	10	2	
t °C	-20 ... +100		
pH	5 - 13		
g/cm ³	1.45		

Main application

- Centrifugal pumps
- Agitators

Suitable for

- Universal use in lower temperature range
- Pulp and paper industry
- General plant maintenance
- Sewage plants



Form of delivery

This packing can be manufactured from 6 to 30 mm square as well as in intermediate, inch sizes and special measurements.

- 06 - 09 mm on 1 kg spool
- 10 - 15 mm on 2,5 kg spool
- 16 - 25 mm on 5 kg spool

Special length on request.

1 kg of packing of the following cross-sections is equivalent to displayed meter lengths:

Size mm	Meter	Size mm	Meter
6	19.2	15	3.1
6.4 [1/4"]	17.1	16 [5/8"]	2.7
8 [5/16"]	10.8	18	2.1
9.5 [3/8"]	7.6	19 [3/4"]	1.9
10	6.9	20	1.7
11 [7/16"]	5.6	22 [7/8"]	1.4
12	4.8	25 [1"]	1.1
13 [1/2"]	4.3		
14 [9/16"]	3.5		

All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.

Please note that the technical values cannot be used all at the same time in their maximum values.