



P 84

Para-Aramid Fiber Packing with with graphite grease impregnation and Run-In Lubricant

Characteristics

- Wear-resistant universal packing
- Good structural strength
- Recommended shaft surface hardness: HRC 50
- Smooth braiding for damaged shaft surfaces
- Very good price-performance ratio



Operating range

p [psi]	220	940	
v [fpm]	1,970	390	
t °F	-4	...	+300
pH	2	-	12
lb/in ³	0.0542		

Main application

- Centrifugal pumps
- Mixer

Suitable for

- Waste water technology
- Pump industry

Variant

- P7 / TP7 with PTFE Blocking Agent and Paraffin Run-In Lubricant
- P7A with PTFE, without lubricant for valves



Form of delivery

This packing can be manufactured from 6 to 40 mm / 1/4" to 1.5" square as well as in intermediate, inch sizes and special measurements.

- 06-09 mm/1/4"-5/16" on 2 lbs spool
- 10-15 mm/3/8"-9/16" on 5 lbs spool
- 16-25 mm/5/8"-1" on 10 lbs spool

Special length, pre-cut or die formed rings on request.

1 lbs of packing of the following cross-sections is equivalent to displayed lengths in feet:

Size	Feet	Size	Feet
6	27.6	15	4.4
6.35 [1/4"]	24.6	16 [5/8"]	3.9
7	20.2	18	3.1
8 [5/16"]	15.5	19 [3/4"]	2.7
9.5 [3/8"]	11.0	20	2.5
10	9.9	22 [7/8"]	2.0
11 [7/16"]	8.2	25 [1"]	1.6
12	6.9		
12.7 [1/2"]	6.1		
14 [9/16"]	5.1		

All technical information and advice is based on our experience and will be given most conscientiously but without any liability.

Indication and figures are for guidance only and need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.

Please note that the technical values cannot be used all at the same time in their maximum values.

ProPack AG

Rudolf-Diesel-Ring 28 . 82054 Sauerlach

Fon ++49 (0) 8104 6640 0 . Fax ++49 (0) 8104 6640 44
propack@propack.ag

www.propack.ag
TECHNOLOGY MADE IN GERMANY